

KORZITE COATINGS INC.

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT INFORMATION.

Material Name/Identifier: SR/CLN-Up

Manufacturer's Name: Korzite Coatings Inc.
7134 Wellington Rd.124
Guelph, Ontario
N1H 6N3

Emergency Telephone Numbers: During business hours 519 821 1250
After business hours 613 996 6666

Trade Name: Toluol
Product Class: Solvent

SECTION II - HAZARDOUS INGREDIENTS OF MATERIAL

Toluene	60.0 – 100.0 %	108-88-36	T.L.V. 100 PPM	Oral (Rat) 5 g/Kg Dermal (RbT) 14g/Kg	8000 PPM/4 hr.
---------	----------------	-----------	----------------	--	----------------

SECTION III - PHYSICAL DATA FOR MATERIAL

Appearance and Odour: Clear liquid with the odour of solvent present.

Evaporation Rate: Faster than n-Butyl Acetate (n-Butyl Acetate = 1)

% Volatile by Volume: 100%

Specific Gravity: 0.87 +/- 0.1

Boiling Point: 110 degrees Celsius

pH: Not applicable

SECTION IV - FIRE AND EXPLOSION HAZARDS OF MATERIAL

Flammability: Flammable.

Means of Extinction: Foam, Carbon dioxide or dry chemical.

Special Procedures: Wear self-contained breathing apparatus with a full face piece. Use water spray to cool near by containers and structures exposed to fire.

Flashpoint and Method: 7 degrees Celsius T.C.C.

Hazardous Combustion Products: Carbon Monoxide, Carbon Dioxide, and various Hydrocarbons.

Unusual Fire and Explosion Hazards:

Closed containers may explode when exposed to extreme heat or fire. Vapours are heavier than air and may travel along the surface to distant sources of ignition and flashback. May decompose under fire conditions emitting irritant and/or toxic gases.

SECTION V - REACTIVITY DATA

Chemical Stability: Stable

Incompatibility to Other Substances: No

Reactivity and Under What Conditions: Avoid high temperature exposure.

Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide, and various Hydrocarbons.

Hazardous Polymerization will not occur.

SECTION VI - TOXICOLOGICAL PROPERTIES OF PRODUCT

Route of Entry: Skin contact, skin absorption, eye contact, inhalation, and ingestion.

Effects of Acute Exposure to Product:

Skin: Can cause irritation of skin, may also cause defatting, drying and cracking of the skin.

Eyes: Can cause irritation of eyes, may also cause redness and pain.

Inhalation: Can cause irritation of respiratory tract, may also cause central nervous system (CNS) depression which is characterized by headache, dizziness, drowsiness, nausea, vomiting and incoordination.

Ingestion: Can cause irritation, a burning sensation of the mouth, throat and respiratory tract and abdominal pain.

Effects of Chronic Exposure to Product:

Skin: Can cause dermatitis, defatting, and sensitization to skin.

Eyes: Can cause blurred vision, tearing and redness, corneal damage and conjunctivitis.

Inhalation: Can cause mucous membrane irritation, central nervous system depression, respiratory problems, intoxication, confusion, loss of consciousness and asphyxiation.

Ingestion: Can cause nausea, vomiting, diarrhea and neural dysfunction.

Irritancy of Product: The product can cause irritation to skin, eyes, respiratory tract and digestive system.

Sensitization to Product: Not Established.

Carcinogenicity: Not applicable.

SECTION VII - PREVENTIVE MEASURES

Personal Protective Equipment:

Gloves: Chemical resistant gloves should be used. Neoprene or rubber glove may be used for exposure of short duration.

Respiratory: An air-purifying respirator equipped with organic vapour cartridges (vapour respirator). An air-supplied respirator is needed for higher concentration of volatile material.

Eye: Chemical safety goggles.

Footwear: Chemical resistant boots.

Clothing: Protective clothing or overalls.

Other: Impermeable apron, face shield.

Engineering Controls:

General ventilation required local exhaust ventilation desirable; electrical and mechanical equipment should be explosion and spark proof.

Leak and Spill Procedures:

Ignition sources such as sparks, open flames or hot surfaces should be removed. Appropriate personal protective equipment should be used. For small spills or drips, mop or wipe up and dispose of in DOT-approved waste containers. For large spills, contain by diking with soil or other non-combustible absorbent materials and then pump into DOT-approved waste container; or absorb with non-combustible absorbent material. Place residue in DOT-approved waste containers. Keep out of sewers, storm drains, surface waters and soil.

Waste Disposal:

Dispose of contaminated product and materials used in cleaning up spills or leaks in a manner approved for this material. Consult appropriate Federal, Provincial and Local regulatory agencies to ascertain proper disposal procedures.

Handling Procedures and Equipment:

Keep containers closed. Avoid heat, open flames, and spark sources. Avoid splash-filling. Ground and bond equipment and container(s) to prevent a static charge build up.

Storage Requirements:

Store in cool, well-ventilated area. Avoid excessive heat exposure.

Regulatory Classification:

HMIS Rating:			
Health:	Flammability	Reactivity	Personal Protection
3	3	0	H
HMIS Classification:	B2, D2B, Flammable liquid.		
Shipping Name:	Paint		
Hazard Class:	Class 3		
Special Shipping Information:	UN Number - 1294		
Packing Group:	II		

SECTION VIII - FIRST AID MEASURES.

Skin: Wash contaminated skin with mild soap and water. Remove contaminated clothing.

Eye: Flush eyes immediately with water for 15 minutes especially under lids. Seek Medical attention.

Inhalation: Remove victim to fresh air, restore and support continued breathing. Seek Medical attention.

Ingestion: Do not induce vomiting. Seek Medical attention immediately.

General Advise: Guard against aspiration of the product into the lungs.

SECTION IX - PREPARATION DATE OF M.S.D.S.

Additional Information / Comments:

The information contained here may not be valid if this product is used:

In conjunction with any other chemical product.

For a purpose other than intended.

In unusual conditions.

The information contained herein is based on information available at the indicated date of preparation. This M.S.D.S. supersedes all previous M.S.D.S.'s for this product.

Sources Used:

1. Raw Material M.S.D.S.'s from suppliers.
2. M.S.D.S. guidelines from C.P.C.A.
3. Guide to Canadian Transportation of Dangerous Goods Act and Regulations.
4. The W.H.M.I.S. Handbook.

Prepared By:

Date of Preparation: May 3, 2005